CAVIUS























PRODUCT NAME: CAVIUS SMART REMOTE PRODUCT NUMBER: 9001

PRODUCT DATA:

DEVICE TYPE:

Smart remote with emergency light.

USAGE:

Designed to alert with a rapid flashing warning light, vibration and buzzing when alarming and to remote control the CAVIUS Wireless alarms Family. Torch function to find escape routes at night.

FUNCTION:

The alarm conditions is indicated by a stroboscopic flashlight.

A normal flashlight can also be activated by pressing the side button.

Flashlight will flash at 2 Hertz (2 times each second) to avoid photo sensitive epilepsy to be triggered.

INSTALLATION POSITION:

The body of the remote has a build-in magnet so that the remote can be installed on metal surfaces.

A lanyard can also be added to the end of the product so the remote can hang from a hook.

PRODUCT DIMENSIONS:

D: 58 mm. x W: 140 mm.

PRODUCT WEIGHT:

Base remote weight: 48 g.

OPERATION AC/DC:

DC

BATTERY TYPE:

3 x AAA batteries supplied with the Smart Remote.

LOW BATTERY INDICATION:

A short acoustic beep will sound to notify a low battery voltage.

INTERLINK FREQUENCY:

868MHZ

SIGNALS:

Transmits RF signals to the CAVIUS Wireless Family at alarm.

INTERLINK RANGE:

Minimum 100m in open field as a receiver, and within short range to silence an alarm. Range depends on the building materials and will need to be tested in each individual case.

SOUND:

Audible indicator.

PUSH BUTTON:

The Smart Remote is equipped with 3 switches:

Sliding learn switch to connect to other alarms in the wireless family.

Test/hush button at the end. Torch button on the side.

WARRANTY:

10 year

APPROVALS:

EN60065

RED

RoHS

REACH

CE TESTING INSTITUTE:

SGS

AWARDS:



red<mark>dot</mark> design award winner

ASSOCIATIONS AND COMMITTEES:

CAVIUS is member of the NF292 committee.

CAVIUS is member of GIFSID, manufacturers' association of domestic fire safety equipment.



PRODUCT NAME: CAVIUS SMART REMOTE

PRODUCT NUMBER: 9001

PRODUCT DATA:

OPERATING TEMPERATURE:

+4°C to +38°C (tested from 0 degrees to 55 degrees)

OPERATING HUMIDITY:

Up to 90% RH non-condensing

STORAGE TEMPERATURE:

-20°C to +60°C

STORAGE HUMIDITY:

Up to 93% RH non-condensing

QUALITY ASSURANCE:

POWER CONSUMPTION:

100% tested

BATTERY VOLTAGE AND INTERNAL RESISTANCE:

100% tested

ALARM FUNCTION:

100% tested

INTERCONNECTION:

100% tested

VISUAL APPEARANCE:

100% tested

PACKING CONTENT:

100% tested

CONTACT

www.cavius.com

MANUFACTURER

Manufacturer: CAVIUS Aps, DK8600

CAVIUS

